

KDG 18 NW7



Snabbkoppling hona (NW7,2) G 1/8"(utv), mässing

Betyg: Inte betygsatt ännu

Pris

Pris 96,18 kr

Pris utan moms 76,94 kr

Rabatt

Momsbelopp 19,24 kr

[Ställ en fråga om denna produkt](#)

Beskrivning

Technical data

Version Standard

Material Brass

actual nominal width [mm] 7.2

Thread external G 1/8"

Note RoHS-compliant

Weight 70 g / pc.

Further information

Customs duty number: 84812090

Description

Materials:

Housing: Brass, nickel-plated brass, steel hardened, 1.4305, seal: NBR (stainless steel: Viton)

Temperature range:

-20°C to max. +100°C (stainless steel: -15°C to max. +200°C, plastic sleeve max. +80°C)

Operating pressure:

0 - 35 bar, as well as low vacuum, CEJN couplings: 0 - 16 bar

Flow***:

Ball lock: 1100 l/min (option -BA: 800 l/min), ball lock: 1800 l/min, CEJN coupling: 2100 l/min, ball lock/plastic sleeve: 2100 l/min

Warning:

Only the following combinations of coupling plug and coupling socket are possible:

Shut-off coupling socket BA with coupling plug without valve

Shut-off coupling socket BA with shut-off coupling plug BA

Compatible with**:

Rectus (25, 26, 1600, 1625), TEMA (1600), CEJN (320), JWL (520, 530, 560), Legris (25, 26), Parker (PE, PEF), Prevost (E ... 07) and many other German brands

Optional:

Use for double-sided shut-off plug -BA, NPT-thread -NPT

***6 bar input pressure, 0,5 bar pressure difference

**Names and designations are partly trademarks of the manufacturers entered.

*SW 22 with PTFE coated G-thread, optionally with SW 24 and undetachable gasket: KDG 12 NW7-SW24

All data are to be understood as non-binding reference values! We do not assume liability for any data selection not confirmed in writing. Unless otherwise specified, pressure values refer to liquids from Group II at +20°C.