

GE 15 LR MSV



Rak skärningskoppling. 15 L-R 1/2", nickelplätterad mässing

Betyg: Inte betygsatt ännu

Pris

Pris 84,81 kr

Pris utan moms 67,85 kr

Rabatt

Momsbelopp 16,96 kr

[Ställ en fråga om denna produkt](#)

Beskrivning

Technical data

Model series light model series

Tube Ø outer [mm] 15 L

Screw-in thread R 1/2"

Operating pressure with hard copper tube [Bar] 70

Temperature range [°C] -60 to +300

Further information on GE15LRMSV

Weight 105 g / Pcs

GTIN 4050571319557

Customs duty number 74122000

RoHS compliant Yes

Description - Straight cutting ring fit. 15 L-R 1/2", nickel-plated brass

Materials:

Body: nickel-plated brass, cutting ring: brass

Raka gängade kopplingar: GE 15 LR MSV

Temperature range:

-60°C up to max. +300°C (swivel screw connections: -20°C up to max. +80°C)

Recommended raw materials:

Copper, polyamide (with reinforced sleeve)

Note:

When using soft copper tube a correction factor of 0.65 must be used (pressure x 0.65). When using polyamide tube the operating pressure of the tube applies.

All data are to be understood as non-binding reference values! We do not assume liability for any data selection not confirmed in writing. Unless otherwise specified, pressure values refer to liquids from Group II at +20°C.