

GAI 10 LR MSV



Rak skärningskoppling. 10 L-G 1/4", nickelplätterad mässing

Betyg: Inte betygsatt ännu

Pris
Pris 85,83 kr

Pris utan moms 68,66 kr

Rabatt

Momsbelopp 17,17 kr

[Ställ en fråga om denna produkt](#)

Beskrivning

Technical data
Model series light model series
Tube Ø outer [mm] 10 L
Female thread G 1/4"
Operating pressure with hard copper tube [bar] 115
Temperature range [°C] -60 to +300
Further information on GAI10LRMSV
Weight 42 g / Pcs
GTIN 4050571480189
Customs duty number 74122000
RoHS compliant Yes
Description - Screw cutting ring ftt. 10 L-G 1/4", nickel-plated brass
Materials:
Body: nickel-plated brass, cutting ring: brass

Raka inv. gängade kopplingar: GAI 10 LR MSV

Temperature range:

-60°C up to max. +300°C (swivel screw connections: -20°C up to max. +80°C)

Recommended raw materials:

Copper, polyamide (with reinforced sleeve)

Note:

When using soft copper tube a correction factor of 0.65 must be used (pressure x 0.65). When using polyamide tube the operating pressure of the tube applies.

All data are to be understood as non-binding reference values! We do not assume liability for any data selection not confirmed in writing. Unless otherwise specified, pressure values refer to liquids from Group II at +20°C.