4 SP 12



4 SP hydraulslang, EN 856, DN 12

Betyg: Inte betygsatt ännu
Pris
Pris 800,11 kr

Pris utan moms 640,09 kr

Rabatt

Momsbelopp 160,02 kr

Ställ en fråga om denna produkt

Beskrivning

Technical data

DN [mm] 12

Hose Ø inside [mm] 12,7

Hose Ø external [mm] 24,2

Operating pressure [bar] 420

Burst pressure [bar] 1750

Min. bend radius [mm] 120

Size parameter 8

Further information on 4SP12

Weight 900 g / m

GTIN 4050571199036

Customs duty number 40092100

RoHS compliant Yes

Description - 4 SP hose, EN 856, DN 12

4 SP - 4 dubbel stålarmering, EN 856: 4 SP 12

Materials:

Synthetic internal and external rubber

Temperature range:

-40? to max. +100?, temporary up to max. + 125?

Operating range:

high pressure hydraulic systems

Resistance:

Hydraulic oils on basis of mineral oil, air*, water, lubricants and fuels, bio oils

Delivered as:

Due to the manufacturing process we cannot exclude that the goods will be supplied in pieces. We attempt to deliver max. 3 pieces, where none of the pieces is shorter than 3 meters.

*hose must be pricked

All data are to be understood as non-binding reference values! We do not assume liability for any data selection not confirmed in writing. Unless otherwise specified, pressure values refer to liquids from Group II at +20°C.